



Article No.: A46007

Articlename: SYS986503200 AZURA 862 HPG System DAD 2.1L

HPLC 862 bar system with binary HPG pump and 3D diode array detector System Proposal

Eluent delivery

The **Pump P6.1L with a HPG configuration** features a solvent selection valve to set up to 4 solvents to the system of which two can be blended simultaneously. The internal degassing unit will prevent air bubbles in the system. Every P 6.1L comes with an attached mixing chamber, which can be changed to a larger volume depending on the applications needs.

Sample Injection

The **Autosampler 6.1L** can inject 0.1 – 5000 µl to have a large flexibility. Using standard vials or two microtiter plates will give you a maximum sample capacity of up to 768 samples or 108 vials.

Column thermostating

The **Column thermostat CT 2.1** is suitable for column thermostatzation above and below room temperature. The instrument operates with a microprocessor controlled Peltier element for exact temperature settings.

Chromatography data system

KNAUER **ClarityChrom®** is a powerful, yet easy-to-use chromatography software for instrument control, data acquisition and data processing. It is an economical solution compared to other more complex chromatography software while still offering FDA 21 CFR Part 11 compliance.

Detection

The detector **DAD 2.1L** features a novel light path and flow cell architecture with improved handling and excellent performance. This Diode array detector can be used in the wavelength range of 190-700 nm.

This AZURA Analytical system can be customized with several detectors

- The diode array detector **DAD 6.1L** covers all conceivable applications with a spectral range of 190-1000 nm. With its novel light path and optimized flow cells, it is one of the most powerful devices on the market.

Help

or **MWD 2.1L** is an 8 channel, sensitive multiwavelength detector with high performance with easy handling at an affordable price. This

[Schedule your free consultation now](#)

multiwavelength detector can be used in the wavelength range of 190-700 nm.

- The variable single wavelength UV/VIS detector **UVD 2.1L** comes with an installed deuterium lamp which covers a wavelength range from 190 to 750 nm. It is a competitively priced detector for routine HPLC applications including fast LC methods.

System Configuration: HPLC 862 bar system with binary HPG pump and

3D diode array detector 190-700 nm

3D diode array detector 190-1000 nm

Variable multi wavelength UV/VIS detector

Variable single wavelength UV/VIS detector

Fluorescence Detector

System code

986503200

986603200

986403200

986203200

986803200

Customized configurations like combinations of several detectors are also available. Please contact us!



[Schedule your free consultation now](#)

TECHNICAL DATA

Analytical system

Application area	HPLC
Pump system	Gradient
Gradient	Binary HPG
Injection	Autosampler
Detector	Diode array detection DAD
Software	ClarityChrom, Mobile Control
Pressure	862 bar
Column thermostat	Yes

[Schedule your free consultation now](#)

SYSTEM COMPONENTS



AZURA Eluent tray E 2.1L

Article No. AZC00

AZURA® Eluent tray E 2.1L for AZURA® devices with a capacity of 6 x 1 l bottles or 4 x 2.5 l bottles or 2 x 5 l bottles, (delivery without bottles)

Type : **Eluent tray**



AZURA P 6.1L

Article No. APH35EA

AZURA® Pump P 6.1L (HPG), with 10 ml pump head (stainless steel), degasser and mixer (100 µl)

Max. flow rate : **10 ml/min**

Pump head materials : **Stainless Steel**

Gradient : **High pressure gradient (binary)**

Pump features : **Active pulsation compensation, RFID for automatic pump head detection, Integrated pressure sensor, Purge valve (manual), Leak management, Piston seal wash**

Maximum delivery pressure [MPa] : **86 MPa**



Autosampler AS 6.1

Article No. AAA50AA

AZURA® Autosampler AS 6.1L analytical HPLC autosampler, 862 bar

Maximum back pressure : **862 bar**

Sample loop : **100 µl**

Sample tray cooling : **None**

Autosampler Flow Path : **Analytical**



Set of eluent supply bottles for analytical HPG systems

Article No. A5324-4

Set of eluent supply bottles, 2 x 1 L bottles and 1 x 250 ml bottle for piston backflushing, includes closed screw caps

[Schedule your free consultation now](#)

**Eluent waste kit for AZURA Analytical systems**

Article No. A59258

Eluent waste kit for all AZURA Analytical systems, incl. filter, waste can and cap

**Screw neck vial set N9, 1.5 ml, clear, wide opening, 100x**

Article No. A0638-6

Vials: Screw neck vials N9 (ø 11.6 mm), 1.5 ml, clear glass, flat bottom, wide opening, with label & scale

Caps: Screw caps blue with septum silicone beige/PTFE white
100 pcs each**AZURA CT 2.1**

Article No. ATC00

Column thermostat AZURA CT 2.1 for constant temperatures and reproducible results

Temperature range : 5–85 °C

**AZURA Detector DAD 2.1L**

Article No. ADC01

AZURA® Detector DAD 2.1L Diode array detector DAD 2.1L without flow cell 190 - 700 nm, incl. test cell

Detector type : **Diode array detector**Detection channels : **8 (Digital)/4 (Analog)**Wavelength range : **190 - 700 nm**Number of diodes : **256**Linearity : **> 2.0 AU at 274 nm (ASTM E1657-98)**[Schedule your free consultation now](#)



Analytical KNAUER PressureProof UV Flow Cell Cartridge

Article No. AMC38

10 mm path length, 10µl, 1/16", 300 bar, PressureProof Flow cell cartridge for AZURA® Detector DAD/MWD

Flow cell type : **Analytical UV flow cell**

Path length : **10 mm**

Capillary connection : **1/16"**

Max. flow rate : **20 ml/min**

Flow cell volume : **10 µl**



ClarityChrom 8.2.3 - Workstation, autosampler control included

Article No. A1670

ClarityChrom® single instrument license for one time base

Software name : **ClarityChrom**




ClarityChrom 8.2.3 - PDA extension

Article No. A1676

ClarityChrom® option for PDA data processing

Software name : **ClarityChrom**



Chromatography Workstation: PC plus monitor

Article No. A13120

Desktop PC (SFF) for PurityChrom® and ClarityChrom® with 24" monitor, English edition Windows 10 Prof. 64-bit English, Intel® Core™ i5, 8 GB RAM, 256 GB SSD, two network cards




Router 8-Port LAN, WiFi, international

Article No. A64809INT

WiFi router, 8x LAN GBit RJ-45 ports, 1x WAN GBit RJ-45 port, power plug UK, US or AUS


[Schedule your free consultation now](#)



AZURA® Analytical K-Connect start-up kits, stainless steel, 1/32" capillaries with fitting sleeves for 1/16" connections

Article No. AZF50

Set of precut capillaries 0.18 mm ID, fittings, connectors and adapters, yellow



Tool kit AZURA

Article No. A1033

Tool Kit AZURA® for systems with PEEK or pre-cut capillary kits

Type : **Tool kit**

DOCUMENTS AND MORE INFORMATION

AZURA Analytical HPLC and UHPLC brochure

AZURA Analytical HPLC/UHPLC brochure, V7852US, V4, 2017-08

Brochure English

AZURA System Selection Guide (V7857US)

System suggestions for analytical HPLC/UHPLC, FPLC, preparative LC and sample preparation systems. English language, V7857US

Brochure English

[Schedule your free consultation now](#)

RELATED PRODUCTS

**High-End Diode Array Detector
for Liquid Chromatography and
Process Technology**

AZURA® Detector DAD 6.1L
Diode array detector DAD 6.1L
without flow cell 190 - 1000 nm,
incl. test cell

Article No.: ADC11

**Versatile Multi Wavelength UV-
Detector for Liquid
Chromatography and Process
Technology**

AZURA® Detector MWD 2.1L
Multiwavelength detector MWD
2.1L, without flow cell 190 - 700
nm, incl. test cell

Article No.: ADB01

**Superior Single Wavelength UV-
Detector for Liquid
Chromatography and Process
Technology**

AZURA® Detector UVD 2.1L with
deuterium lamp without flow cell,
incl. test cell

Article No.: ADA01XA

**Basic Fluorescence Detector for
Liquid Chromatography**

Fluorescence detector RF-20 A
200 - 650 nm incl. accessories
and flow cell

Article No.: A59200

[Schedule your free consultation now](#)



Do you need more details or a quote?

We are happy to help you



+49 30 809727-0



sales@knauer.net

Technical data or prices are subject to change without notice. Prices may vary by country and do not include taxes, customs duties or delivery.

All trademarks are the property of their respective owners. Our general terms and conditions apply: www.knauer.net/terms

[Schedule your free consultation now](#)