



Product specification

MAS · Multi protocol stainer

Item No.: 14000500



Specifications

Max. number of staining protocols:	20 / 12 parallel operating staining programs
Max. number of program steps:	40
Free choice for every step:	station, time (from 1 sec. to 59 min.)
Drip collection:	adjustable drain time combined with a patented drip collection technology avoids carryover of solvents
Drain time:	0 to 9 sec.
Compatible to all coverslipping machines in the market	
Operating temperature range	+10 to +35 °C
Operating humidity	max. rel. 80 % non-condensing
Storage temperature range	+5 to +55 °C
Storage humidity	max. rel. 80 % non-condensing
Number of stations:	44 including: 4 loading stations 4 unloading stations 6 water stations for running water optional: 2 drying stations (temperature adjustable from +40 °C to +80 °C) 4 water stations 30 staining stations with agitation
Contents of solvent containers:	360 ml, can be reduced to 260 ml
Dimensions (W / D / H):	1,210 x 670 x 640 mm

Specifications

Weight:	115 kg
Electrical parameters:	100-230 V / 50/60 Hz / 100 VA

Standard components

Loading stations (4 pcs.)
Unloading stations (4 pcs.)
Staining cuvettes (30 pcs. à 360 ml)
Washing cuvettes (6 pcs.)
Slide baskets (4 pcs. up to 30 slides each)
Carbon filter
Mains cable
Manual

T: (763) 712-8717
M: sales@gmi-inc.com